R76LT



Tire Changer SKU# 5140144 Tilt Back, 30" Capacity, 110 or 220V, 50/60hz Questions? Contact BendPak's Sales Team sales@bendpak.com | 1-800-253-2363 Monday - Friday, 7AM to 4:30PM PST

Performs Masterfully on a Wide Variety of Wheels

The Ranger R76LT <u>tire changer</u> performs masterfully on a wide variety of wheels, including OEM configurations. This equipment has ergonomic controls, a tilt-back tower design, advanced clamp positioning and so much more.

This professional-grade Ranger R76LT is a tilt-tower machine. Its large turntable provides an internal clamping capacity of 30" and an external clamping capacity of 28". A sturdy body, rigid 45 mm hexagonal vertical shaft and hardened-steel horizontal outrigger support arm eliminate flex during all tire service procedures to reduce the likelihood of expensive wheels getting damaged. Bead seating and tire inflation is simple and effortless with Ranger's exclusive TurboBlast[™] portable bead seating system.

Specifications

3 HP (220 VAC 50-60 HZ)
Electric / Air
110-175 PSI (8-12 BAR)
4 Clamps - Internal / External
Dual Pneumatic Cylinders
Adjustable Pneumatic Blade
Tilt-Back
Pneumatic / Locking
TurboBlast™
10" – 30" (254 mm - 762 mm)
9" – 28" (229 mm - 711 mm)
4" – 18" (102 mm – 457 mm)
1.5" – 16" (38 mm – 406 mm)
43" (1,092 mm)
886 lbs. (403 Kg)



Standard Features

- Inflation System
- Inflation Gauge & Air Dump Valve
- Inflation Pressure Regulator/Limiter
- Water Filter
- Oiler / Lubricator
- Soap Brush

- Air Regulator
- Bead Tool/Tire Iron
- Alloy-Steel Mount-Demount Head
- Nylon Mount-Demount Head
- Large Soap Bucket
- Tool Tray / Storage